

Automatic Address Setting Method; Displaying Indoor / Outdoor Unit Combination Numbers - Sanyo KH2442 / CH2442 Service Manual

Split system air conditioner


1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18

19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68

69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118

119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168

169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202



•

[Table of Contents](#)

•

Troubleshooting

•

Bookmarks



(7) Automatic Address Setting Method

— For group control and central control with multiple outdoor units —

Carry out automatic address setting with the remote controller.

(1) All auto. address operation

1 Press the **(7) Automatic Address Setting Method** — For group control and central control with multiple outdoor units — the same time for more than 4 seconds.

2 Press the **Carry out automatic address setting with the remote controller.**

Section CODE No. AA (CODE No. AA: All Auto. address operation)

(1) All auto. address operation
① Press the  and  () buttons at

(8) Displaying Indoor Combination Numbers

Display the indoor / outdoor automatic address setting.

(1) When installing multiple unit address numbers and address numbers and c

1

After addresses are automatically set in order for the outdoor units from No. 1 to No. 30, the system returns to the normal stopped state.

(2) Individual auto. address operation for each refrigerant circuit

(7) Automatic Address Setting Method

1




To select each refrigerant circuit individually — For group control and central control with multiple outdoor units —

2

and set addresses automatically, press the time for more than 4 seconds, then press the


Carry out automatic address setting with the remote controller.

(1) All auto. address operation

CODE No. A1. ① Press the  and  () buttons at the same time for more than 4 seconds.

3

Select R.C. No. which you want to execute the auto. address operation with button.

② Press the  button after confirming the CODE No. AA (CODE No. AA: All Auto. address operation).

After addresses are automatically set in order for the outdoor units from No. 1 to No. 30, the system returns to the normal stopped state.

3

Press the






operation will start. CODE No. changes from flashing to ON state.


(2) Individual auto. address operation for each refrigerant circuit

4 ① To select each refrigerant circuit individually and set addresses automatically, press the

4


the alarm message will display. Check and remove the cause. If you want to interrupt the operation, press the

 and  () buttons at the same time for more than 4 seconds, then press the  () button once to set CODE No. A1.

(CODE No. A1: Auto. address operation) ② Select R.C. No. which you want to execute the auto. address operation with  button.

5

If the auto. address operation finishes, the display will disappear.

Press the  button. The auto. address operation will start. CODE No. changes from flashing to ON state.



6

Execute the operation of the other R.C. line in the same way by following the above

steps 2 to 3.

4

Complete the auto. address operation by pressing the

④ If the error is happened during the operation, the alarm message will display. Check and remove the cause. If you want to interrupt the operation, press the  button then the unit stands in waiting mode (Press the  button)

NOTE

Required time for auto. address operation:

In case of group control : If the auto. address operation finishes, the display will disappear.

4.

(8) Displaying Indoor Combination Numbers




Display the indoor / outdoor automatic address setting.


(1) When installing multiple unit address numbers and check location (near the based magic marker or that the individual indoor units can be checked

Example:

Outdoor Unit 1 – Indoor
Outdoor Unit 2 – Indoor

(2) This is necessary for m these.

*Check indoor unit address controller. Press the  seconds and check the the  button. (Each  button, the address 2-1, 2-2, ...) The fan for indoor unit runs and label (If there is 1 outdoor unit 1-2, ...)

When you press the  returns to normal remote

In case of central control : max. about 20 min. for
 and
 (
 button after confirming the
 and
 (
) buttons at the same

(7) Automatic Address Setting Method

For group control and central control with multiple outdoor units —

Carry out automatic address setting with the remote controller.

(8) Displaying Indoor / Outdoor Unit Combination Numbers

Display the indoor / outdoor unit address after automatic address setting.

(1) When installing multiple units, mark the indoor unit address numbers and address operation.

After addresses are automatically set in order for the outdoor units from No. 1 to No. 30, the system returns to the normal stopped state.

(2) Individual auto. address operation for each refrigerant circuit

To select each refrigerant circuit individually and set addresses automatically, press the

(2) This is necessary for maintenance. Always label these.

*Check indoor unit address with the remote controller. Press the

seconds and check the indoor unit address with the

2-1, 2-2, ...) The fan for only the selected indoor unit turns on at high speed, so check which indoor unit runs and label the indoor unit address.

(If there is 1 outdoor unit, the address is 1.) The auto. address operation will start. CODE No. changes from flashing to ON state.

If the error is happened during the operation, the alarm message will display. Check and remove the cause. If you want to interrupt the operation, press the [CL] button then the unit stands in waiting mode (Press the [SET] button).

button for at least 4 seconds. (Each time you press the button, the address changes 1-1, 1-2, ... button again, the system

SM830082 (5) If the auto. address operation finishes, the

(8) Displaying Indoor Combination Numbers

Display the indoor / outdoor automatic address setting.

(1) When installing multiple unit address numbers and check location (near the based magic marker or that the individual indoor units can be checked

Example:

Outdoor Unit 1 – Indoor
 Outdoor Unit 2 – Indoor

(2) This is necessary for these.

*Check indoor unit address controller. Press the [] seconds and check the the [UNIT] button. (Each [UNIT] button, the address 2-1, 2-2, ...) The fan for unit turns on at high speed indoor unit runs and label (If there is 1 outdoor unit 1-2, ...)

When you press the [] returns to normal remote



Table of Contents

[Previous Page](#)
[Next Page](#)

1

...

193

194

195

196

Quick Links:

[Technical Data](#)

[Service Manual](#)

[Unit Specifications](#)

[Troubleshooting](#)

Chapters

[Who Should Use This Manual](#) 3

[2. Processes and Functions](#) 121

[4. Service Procedures](#) 157

Troubleshooting

[Troubleshooting](#) 158

[Check before and after Troubleshooting](#) 159

[General Troubleshooting Flow Chart: Diagnosis and Remedy](#) 160

Related Manuals for Sanyo KH2442 / CH2442

[Air Conditioner Sanyo CH2442 Installation Instructions Manual](#)

Split system heat pump air conditioner (94 pages)

[Air Conditioner Sanyo RCS-SH80UA Instruction Manual](#)

Split system air conditioner (64 pages)

[Air Conditioner Sanyo 26K72R Dimensional Data](#)

Wall mounted type outdoor/indoor unit (1 page)

[Air Conditioner Sanyo C4272R S/C Installation Instructions Manual](#)

Sanyo split system heat pump air conditioner installation instructions (111 pages)

[Air Conditioner Sanyo C4272R Service Manual](#)

Sanyo split system air conditioner service manual (181 pages)

[Air Conditioner Sanyo RCS-BH80UA.WL Instruction Manual](#)

Split system air conditioner (48 pages)

[Air Conditioner Sanyo Mini ECO-i CHXR03652 Service Manual](#)

(93 pages)

[Air Conditioner Sanyo CHDZ07263 Service Manual](#)

(128 pages)

[Air Conditioner Sanyo Mini ECO-i 85464359981002 Installation Instructions Manual](#)

Sanyo air conditioner installation instructions (90 pages)

[Air Conditioner Sanyo CH0951 Technical & Service Manual](#)

Split system air conditioner (98 pages)

[Air Conditioner Sanyo KHS1822 Service Manual](#)

Split system air conditioner (38 pages)

[Air Conditioner Sanyo KHS3632 / CH3632 Service Manual](#)

Split system air conditioner (94 pages)

[Air Conditioner Sanyo 18KHS72 Installation Instructions Manual](#)

Indoor/outdoor unit inverter split system air conditioner (25 pages)

[Air Conditioner Sanyo 09KHS71 Instruction Manual](#)

Inverter-controlled split system air conditioner (50 pages)

[Air Conditioner Sanyo COOL/HEAT Installation Instructions Manual](#)

Split system air conditioner (20 pages)

[Air Conditioner Sanyo KHS1232 Technical Data Manual](#)

(24 pages)

Related Content for Sanyo KH2442 / CH2442

[CHDZ07263 Auto Address Setting](#)

Sanyo CHDZ07263

[XM18AAB Auto Address Setting](#)

Sanyo XM18AAB

[Mini ECO-i SPW-ASR74GXH56\(A/B\) Auto Address Setting](#)

Sanyo Mini ECO-i SPW-ASR74GXH56(A/B)

[SPW-C256VH Automatic Address Setting](#)

Sanyo SPW-C256VH

[SPW-C0705DZH8 Automatic Address Setting \(No Compressor Operation\)](#)

Sanyo SPW-C0705DZH8

[SPW-CR365GXH56 Automatic Address Setting \(No Compressor Operation\)](#)

Sanyo SPW-CR365GXH56

[KHS3632 / CH3632 Automatic Address Setting Method](#)

Sanyo KHS3632 / CH3632

[C4272R Method Of System Address Setting](#)

Sanyo C4272R

This manual is also suitable for:

[Th4242Uh2442Kh3642Uh3642Xh2442Xh3642](#) ... [Show all](#)