





Whirlpool 015-0005 Installation And Operation Manual



1	
Table Of Contents	
2	
3	
4	
5	
6	
7	
8	
9	
10	
11	
12	
13	
14	
15	

---

- 

[Table of Contents](#)

•

Bookmarks

--

[Download this manual](#)

### Quick Links





# PREMIERE WHIRLPOOL

## ***THANK YOU...***

for selecting an Eljer bathing product. Your new bath is shipped to you after careful inspection. The whirlpool

version is completely assembled with pump and circulatory system piping. All you need to finish the installation

are your selected fittings, electrical connections and support bedding material.

To ensure maximum performance and pleasure from this product, please follow the instructions and cautions.

For questions or service issues, please call Technical Support 1-(800) 442-1902.

Please do not contact or return product to the store.

© Eljer 2011

All product names listed herein are trademarks of Eljer unless otherwise noted.



# **INSTALLATION AND OPERATION MANUAL MODEL NUMBERS**

**015-0005, 015-0015, 015-0026,  
015-0066, 015-0076, 015-0077 ,  
015-0305, 015-0309**

1

754764-100 Rev. A



[Table of Contents](#)

[Next Page](#)

1  
2  
3  
4  
5

# Summary of Contents for Whirlpool 015-0005

## [Page 1: Cover](#)

015-0305, 015-0309 THANK YOU... for selecting an Eljer bathing product. Your new bath is shipped to you after careful inspection. The whirlpool version is completely assembled with pump and circulatory system piping. All you need to finish the installation are your selected fittings, electrical connections and support bedding material.

## [Page 2: Table Of Contents](#)

TABLE OF CONTENTS: Cover.....Page 1 Table of Contents.....Page 2 Safety Instructions Notice.....Page 3 Installation, Framing and Post Installation Clean-Up Instructions.....Page 4 Typical Flange & Under Deck Mounting Instructions.....Page 6 General Specifications for Whirlpools.....Page 7 Roughing-in References for All Model Series.....Pages 8 - 10 Electrical Installation Instructions.....Page 11 Total Massage Whirlpools.....Page 12 Operating Instructions.....Page 13...

## [Page 3: Safety Instructions Notice](#)

IMPORTANT SAFETY INSTRUCTIONS INSTRUCTIONS PERTAINING TO A RISK OF FIRE, ELECTRIC SHOCK OR INJURY TO PERSONS READ AND FOLLOW ALL INSTRUCTIONS! WARNING: Risk of personal injury. Do not permit children to use this unit without adult supervision. WARNING: Risk of personal injury. Do not operate this unit without the guard over the suction fitting.

## [Page 4: Installation, Framing And Post Installation Clean-Up Instructions](#)

Installation and Framing Instructions Each bath arrives ready for installation, completely equipped with the pump and plumbing necessary for operation. However, a drain/overflow kit is required for each bath and it is not included. The variety of installations for this bath may require framing procedures other than those shown. Locate studs as required.

[Page 5](#) Mark the final position of the underside of the deck by tracing a line on to the studs (see Figure 1). 2. Remove the whirlpool and attach a 1 x 4 stringer to the studs, with the top of the stringer touching the traced line.

## [Page 6: Typical Flange & Under Deck Mounting Instructions](#)

TYPICAL FLANGE MOUNTING DETAIL SUGGESTED WHIRLPOOL / BATH TYPICAL INSTALLATION - INSTALLATION METHOD CORNER WOOD STUD STUDS WATERPROOF DRYWALL OR CEMENT BOARD TILE ROOFING NAIL 58-1/2" 58-1/2" SEALANT (1486mm) (1486mm) LEVELING 12" STRINGER (305mm) 1 x 3 (25 x 76mm) WOOD...

## [Page 7: General Specifications For Whirlpools](#)

Water / Floor Weight Overflow of Deck: C G x F E x D Overflow: J Loading L 60" (1524mm) 015-0005 A 15-1/4" C 17" 58-1/2" 60" 2-1/4" 418 lb. (190 kg)/ 98 lb. W 32" (813mm) 5' x 32"...

## [Page 8: Roughing-In References For All Model Series](#)

ROUGH-IN REFERENCES CYPRESS MODEL 015-0005 60" (1524mm) 16" (406mm) 40-1/2" (1029mm) 32" 19-1/2" (813mm) (495mm) 9" x 14" (229 x 356mm) FLOOR CUTOUT PROVIDE ACCESS TO PUMP SERVING ON ALL INSTALLATIONS 10-1/4" (260mm) MADISON MODEL 015-0015 60" (1524mm) 16" (406mm) 40-1/2"...

[Page 9](#) ROUGH-IN REFERENCES CANTERBURY MODEL 015-0026 60" (1524mm) 18" (457mm) 44-1/2" 36" (1130mm) (914mm) 24-1/2" (622mm) 9" x 14" (229 x 356mm) FLOOR CUTOUT PROVIDE ACCESS TO PUMP 8-1/4" (209mm) TRIANGLE MODEL 015-0066 35-1/2" (902mm) 60" (1524mm) PROVIDE ACCESS TO PUMP SERVING ON 35-1/2"...

[Page 10](#) ROUGH-IN REFERENCES EMBLEM MODEL 015-0076 EMBLEM TOTAL MESSAGE MODEL 015-0077 72" (1829mm) 18" (457mm) 51-1/2" 36" (1308mm) 21-1/2" (914mm) (546mm) 9" x 14" (229 x 356mm) FLOOR CUTOUT PROVIDE ACCESS TO PUMP SERVING ON ALL INSTALLATIONS 10-1/2" (267mm) PATRIOT MODEL 015-0309/0305 (Right hand version shown) 60"...

## [Page 11: Electrical Installation Instructions](#)

AIR SWITCH WHIRLPOOLS The whirlpool should be installed on a 120 vac, 15 amp dedicated circuit. The circuit should be hard-wired from the electrical power supply panel. The circuit must be a three (3) wire circuit from the electrical supply panel. A grounded neutral wire and a third wire, earth ground, are essential.

## [Page 12: Total Massage Whirlpools](#)

TOTAL MESSAGE WHIRLPOOLS The whirlpool pump and blower should be installed on a 120 vac, 20 amp dedicated circuit. The circuit should be hard-wired from the electrical power supply panel. The circuit must be a three (3) wire circuit from the electrical supply panel.

## [Page 13: Operating Instructions](#)

TOTAL MESSAGE Total Massage units are a combination of a whirlpool and air bath. The Total Massage control pad contains six (6) buttons. The top three controls on the "Therapy Control Center" operate the whirlpool and the bottom three controls operate the air system.

## [Page 14: Cleaning And Maintenance](#)

Your Eljer whirlpool is designed to give you many years of pleasure with reasonable care and maintenance. Your new acrylic bathtub is tough, durable and easy to care for. The colors have been formulated to match other Eljer fixtures and enhance your choice of bathroom decorations. The high gloss surface will retain its lasting luster with proper care and maintenance.

## [Page 15: Warranty](#)

This limited warranty does not apply to commercial installations. The warranty for commercial installations is three (3) years. THIS WARRANTY SHALL BE VOID IF THE ACCESS PANEL TO THE WHIRLPOOL IS COVERED IN ANY MANNER CONTRARY TO THE INSTALLATION INSTRUCTIONS. In no event will American Standard be liable for the cost of repair or replacement of any installation materials including but not limited to tiles, marble etc.

This manual is also suitable for:

015-0015015-0026015-0066015-0076015-0077015-0305 ... [Show all](#)